Akuvox C313N Datasheet

Premium touch screen for your home

The Akuvox C313N multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.

At a Glance

- Ultra-clear, stylish appearance;
- Thin profile and small footprint;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Two-way audio communication with other units in the network;
- Powered by PoE or external source;
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

Physical & Power

• Front panel: Plastic

• RAM / ROM: 64MB / 128MB

• Display: 7 Inch TFT LCD

• Screen: 7 Inch capacitive touch screen

• Bell in: 1

• Microphone: Single microphone

• Speaker: Single speaker

• Ethernet Ports: 1xRJ45

• POE: 802.3af Power-over-Ethernet

• Power: 12V DC connector

• Tamper Resistant: Support

• Installation: Wall-mounted & Desktop

• Dimension: 200.2x132.2x27.2mm

Working Humidity: 10~90%

• Working Temperature: -10°C ~ +45°C

• Storage Temperature: -20°C ~ +70°C



10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com