Akuvox S562W Datasheet

Premium touch screen for your home

The Akuvox S562W multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.

3:40 AM | 21 ° CONTROL OF CONTROL

At a Glance

- Ultra-clear, stylish appearance;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Completely solve the stability problem of Wi-Fi with Wi-Fi 6;
- Two-way audio communication with other units in the network;
- Powered by PoE or external source;
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

Physical & Power

• Front panel: Plastic

• RAM / ROM: 128MB / 128MB

• Display: 7 Inch IPS LCD

• Screen: 7 Inch capacitive touch screen

• Wi-Fi: IEEE802.11 b/g/n/ax, @2.4GHz

• RS485 Port: 1

• Relay Out: 1

• Bell in: 1

• Alarm Input: 8

• Microphone: -42dB

Speaker: 4Ω / 2W

• Ethernet Ports: 2xRJ45, 10/100Mbps adaptive

• PoE: 802.3af Power-over-Ethernet

• Power: 12V DC connector

Tamper Resistant: Support

• Installation: Wall-mounted & Desktop

• Dimension: 216.4x118.8x21.7mm

• Working Humidity: 10~90%

• Working Temperature: -10°C ~ +45°C

• Storage Temperature: -20°C ~ +70°C

